



HIGH VOLTAGE ELECTRICAL TERMINALS SHORT BARREL ONE HOLES

หางปลาแรงสูงชนิดรูเดียว

(HTS TYPE)

Has provide mechanical strength for heavy duty applications. Suitable for use with cable size from 10-500 SQ.MM.12-35 KV.


Material: Copper tube Cu 99% up

Surface: Tin plated



WIRE CONNECTOR
3LDJ

FILE No: E304648



Item No.	TIS Wire Size mm ²	(DIMENSIONS (MM.))									Q'TY in box
		d2ø	d1ø	Dø	A	B	E	F	H	L	
HTS 10-6	10	6.4	4.5	6.2	9.5	12.0	21.5	7.4	11.5	49.9	100
HTS 10-8		8.4									
HTS 16-6	16	6.4	5.4	7.1	9.5	12.0	25.0	7.4	11.5	53.4	100
HTS 16-8		8.4									
HTS 25-6	25	6.4	6.8	8.8	11.5	15.0	28.5	7.4	13.5	60.9	100
HTS 25-8		8.4									
HTS 25-10		10.5									
HTS 35-6	35	6.4	8.2	10.6	11.5	17.0	32.0	8.0	13.5	65.0	50
HTS 35-8		8.4									
HTS 35-10		10.5									
HTS 50-8	50	8.4	9.5	12.4	13.5	19.0	35.0	10.9	15.5	74.9	40
HTS 50-10		10.5									
HTS 50-12		13.0									
HTS 70-8	70	8.4	11.2	14.7	13.5	21.0	35.0	10.9	17.5	76.9	40
HTS 70-10		10.5									
HTS 70-12		13.0									
HTS 95-8	95	8.4	13.5	17.4	13.5	25.5	38.0	15.8	17.5	84.8	20
HTS 95-10		10.5									
HTS 95-12		13.0									
HTS 120-10	120	10.5	15.0	19.4	14.5	28.0	40.0	18.8	18.5	91.8	20
HTS 120-12		13.0									
HTS 120-14		15.0									
HTS 150-12	150	13.0	16.5	21.2	16.5	30.5	50.0	19.8	20.5	106.8	20
HTS 150-14		15.0									
HTS 150-16		17.0									
HTS 185-12	185	13.0	18.5	23.5	16.5	34.0	50.0	19.8	20.5	106.8	10
HTS 185-14		15.0									
HTS 185-16		17.0									
HTS 240-12	240	13.0	21.5	27.0	16.5	39.5	56.0	24.8	20.5	117.8	10
HTS 240-14		15.0									
HTS 240-16		17.0									
HTS 300-12	300	13.0	23.5	30.0	20.0	43.5	67.0	26.8	24.0	137.8	10
HTS 300-14		15.0									
HTS 300-16		17.0									
HTS 400-12	400	13.0	27.0	35.0	23.0	50.8	67.0	26.8	27.0	143.8	5
HTS 400-14		15.0									
HTS 400-16		17.0									
HTS 500-12	500	13.0	30.0	39.0	23.0	56.0	75.0	33.8	27.0	158.8	5
HTS 500-14		15.0									
HTS 500-16		17.0									