



HIGH VOLTAGE ELECTRICAL TERMINALS SPICE LONG BARREL

สลิปต่อสายแรงสูง

(HTSL TYPE)

Permitted crimp in larger size to assure a strong full tension and high conductive.

suitable to connect cable size from 10-500 SQ.MM. 12-35 KV.

Material: Copper tube Cu 99% up

Surface: Tin plated



LISTED

WIRE CONNECTOR

3LDJ

FILE No: E304648

Item No.	TIS Wire Size mm ²	(DIMENSIONS (MM.))			Q'TY in box
		d1φ	Dφ	L	
HTSL 10	10	4.5	6.2	48.0	100
HTSL 16	16	5.4	7.1	55.0	100
HTSL 25	25	6.8	8.8	62.0	100
HTSL 35	35	8.2	10.6	70.0	50
HTSL 50	50	9.5	12.4	75.0	50
HTSL 70	70	11.2	14.7	75.0	40
HTSL 95	95	13.5	17.4	80.0	40
HTSL 120	120	15.0	19.4	85.0	20
HTSL 150	150	16.5	21.2	105.0	20
HTSL 185	185	18.5	23.5	105.0	10
HTSL 240	240	21.5	27.0	118.0	10
HTSL 300	300	23.5	30.0	140.0	10
HTSL 400	400	27.0	35.0	140.0	5
HTSL 500	500	30.0	39.0	155.0	5

ขั้นตอนการย้าสลิปต่อสาย

ให้ย้าจากในสุดไปปลายสุดแต่ละข้าง



ขั้นตอนที่ 1

ขั้นตอนที่ 1

เตรียมหางปลาและสายไฟ



ขั้นตอนที่ 3

ขั้นตอนที่ 3

ย้าสายที่ปลายสลิป



ขั้นตอนที่ 2

ขั้นตอนที่ 2

ย้าสายจากด้านใน



ขั้นตอนที่ 4

ขั้นตอนที่ 4

ย้าอีกฝั่งในลักษณะเดียวกัน

MAKE THE PERFECT CONNECTION

ELECTRICAL SPLICE

LONG BARREL

(HTSL TYPE สลัฟต่อสายแรงสูง)



ITEM No.		บรรจุ/กล่อง	ราคา/ตัว
HTSL	10	100	38
HTSL	16	100	47
HTSL	25	100	85
HTSL	35	50	110
HTSL	50	50	140
HTSL	70	40	190
HTSL	95	40	210
HTSL	120	20	230
HTSL	150	20	275
HTSL	185	10	300
HTSL	240	10	390
HTSL	300	8	600
HTSL	400	5	700
HTSL	500	5	950
HTSL	630	-	1100