



HIGH VOLTAGE 90° ELECTRICAL TERMINALS LONG BARREL TWO HOLES

หางปลาแรงสูงชนิดรูป 90°


(HRL TYPE)

Suitable for use with cable size from

10-500 SQ.MM. in right angle position

Material: Copper tube Cu 99% up

Surface: Tin plated



Item No.	TIS Wire Size mm²	DIMENSIONS (MM.)													Q'TY in box
		d2ø	d1ø	Dø	A	B	C	E	F	H	L	M	N	T	
HRL 10-6	10	6.4	4.5	6.2	9.5	12.0	15.8	21.5	7.4	16.5	41.8	48.0	29.5	1.1	100
HRL 10-8		8.4													
HRL 16-6	16	6.4	5.4	7.1	9.5	12.0	15.8	25.0	7.4	16.5	41.8	48.9	33.0	1.2	100
HRL 16-8		8.4													
HRL 25-6	25	6.4	6.8	8.8	11.5	15.0	15.8	28.5	7.4	18.5	45.8	54.6	36.7	1.6	100
HRL 25-8		8.4													
HRL 25-10		10.5													
HRL 35-6	35	6.4	8.2	10.6	11.5	17.0	19.0	32.0	8.0	21.5	52.0	62.6	41.0	2.0	50
HRL 35-8		8.4													
HRL 35-10		10.5													
HRL 50-8	50	8.4	9.5	12.4	11.5	19.0	22.7	35.0	10.9	21.5	55.7	68.1	47.2	2.5	40
HRL 50-10		10.5													
HRL 50-12		13.0													
HRL 70-8	70	8.4	11.2	14.7	11.5	21.0	22.7	35.0	10.9	23.5	57.7	72.4	47.7	3.5	40
HRL 70-10		10.5													
HRL 70-12		13.0													
HRL 95-8	95	8.4	13.5	17.4	13.5	25.5	44.4	38.0	15.8	27.5	85.4	100.1	55.6	3.6	20
HRL 95-10		10.5													
HRL 95-12		13.0													
HRL 120-10	120	10.5	15.0	19.4	14.5	28.0	44.4	40.0	18.8	28.5	87.4	106.8	61.0	4.3	10
HRL 120-12		13.0													
HRL 120-14		15.0													
HRL 150-12	150	13.0	16.5	21.2	16.5	30.5	44.4	50.0	19.8	30.5	91.4	112.6	72.1	4.5	10
HRL 150-14		15.0													
HRL 150-16		17.0													
HRL 185-12	185	13.0	18.5	23.5	16.5	34.0	44.4	50.0	19.8	30.5	91.4	114.9	72.2	4.8	4
HRL 185-14		15.0													
HRL 185-16		17.0													
HRL 240-12	240	13.0	21.5	27.0	16.5	39.5	44.4	56.0	24.8	35.5	96.4	123.4	83.6	5.5	4
HRL 240-14		15.0													
HRL 240-16		17.0													
HRL 300-12	300	13.0	23.5	30.0	16.5	43.5	44.4	67.0	26.8	40.5	101.4	131.4	97.0	6.3	2
HRL 300-14		15.0													
HRL 300-16		17.0													
HRL 400-12	400	13.0	27.0	35.0	16.5	50.8	44.4	67.0	26.8	40.5	101.4	136.4	97.8	7.9	1
HRL 400-14		15.0													
HRL 400-16		17.0													
HRL 500-12	500	13.0	30.0	39.0	16.5	56.0	44.4	75.0	33.8	40.5	101.4	140.4	113.3	8.9	1
HRL 500-14		15.0													
HRL 500-16		17.0													