




HIGH VOLTAGE OBTUSE ANGLE ELECTRICAL TERMINALS LONG BARREL TWO HOLES

หางปลาแรงสูงชนิดรูป 135°
(HOL TYPE)
Suitable for use with cable size from
10-500 SQ.MM.in 135°angle position
Material: Copper tube Cu 99% up
Surface: Tin plated

UL LISTED
WIRE CONNECTOR
3LDJ
FILE No: E304648



Item No.	TIS Wire Size mm ²	DIMENSIONS (MM.)													Q'TY in box
		d2ø	d1ø	Dø	A	B	C	E	F	H	L	M	N	T	
HOL 10-6	10	6.4	4.5	6.2	9.5	12.0	15.8	21.5	7.4	16.5	41.8	66.6	21.5	1.1	100
HOL 10-8		8.4													
HOL 16-6	16	6.4	5.4	7.1	9.5	12.0	15.8	25.0	7.4	16.5	41.8	69.7	24.1	1.2	100
HOL 16-8		8.4													
HOL 25-6	25	6.4	6.8	8.8	11.5	15.0	15.8	28.5	7.4	18.5	45.8	77.4	27.0	1.6	100
HOL 25-8		8.4													
HOL 25-10		10.5													
HOL 35-6	35	6.4	8.2	10.6	11.5	17.0	19.0	32.0	8.0	21.5	52.0	87.8	30.3	2.0	50
HOL 35-8		8.4													
HOL 35-10		10.5													
HOL 50-8	50	8.4	9.5	12.4	11.5	19.0	22.7	35.0	10.9	21.5	55.7	96.9	35.0	2.5	40
HOL 50-10		10.5													
HOL 50-12		13.0													
HOL 70-8	70	8.4	11.2	14.7	11.5	21.0	22.7	35.0	10.9	23.5	57.7	100.6	36.0	3.5	40
HOL 70-10		10.5													
HOL 70-12		13.0													
HOL 95-8	95	8.4	13.5	17.4	13.5	25.5	44.4	38.0	15.8	27.5	85.4	128.3	41.6	3.6	20
HOL 95-10		10.5													
HOL 95-12		13.0													
HOL 120-10	120	10.5	15.0	19.4	14.5	28.0	44.4	40.0	18.8	28.5	87.4	142.7	45.9	4.3	10
HOL 120-12		13.0													
HOL 120-14		15.0													
HOL 150-12	150	13.0	16.5	21.2	16.5	30.5	44.4	50.0	19.8	30.5	91.4	155.7	53.8	4.5	10
HOL 150-14		15.0													
HOL 150-16		17.0													
HOL 185-12	185	13.0	18.5	23.5	16.5	34.0	44.4	50.0	19.8	30.5	91.4	157.4	54.1	4.8	4
HOL 185-14		15.0													
HOL 185-16		17.0													
HOL 240-12	240	13.0	21.5	27.0	16.5	39.5	44.4	56.0	24.8	35.5	96.4	172.3	62.6	5.5	4
HOL 240-14		15.0													
HOL 240-16		17.0													
HOL 300-12	300	13.0	23.5	30.0	16.5	43.5	44.4	67.0	26.8	40.5	101.4	188.9	72.6	6.3	2
HOL 300-14		15.0													
HOL 300-16		17.0													
HOL 400-12	400	13.0	27.0	35.0	16.5	50.8	44.4	67.0	26.8	40.5	101.4	193.5	74.2	7.9	1
HOL 400-14		15.0													
HOL 400-16		17.0													
HOL 500-12	500	13.0	30.0	39.0	16.5	56.0	44.4	75.0	33.8	40.5	101.4	205.9	85.8	8.9	1
HOL 500-14		15.0													
HOL 500-16		17.0													