### HD Analog Day/ Night Fixed IR Dome Camera

# Panasonic

# CV-CFW103L CV-CFW103LN

## Smart look Day/ Night Fixed Dome Camera with IR illuminator

**Specifications** 




#### **Key Features**

- High-performance CMOS image sensor.
- Support 720p@25fps (PAL)/ 30fps (NTSC)
- Support 75-3\* coaxial cable transmission over 800m.
- High speed & long distance real-time transmission.
- Support ICR for day time and night time operation.
- Support auto exposure, auto white balance, auto electronic shutter and auto gain function.
- Support DC12V power supply.
- IP66 compliance.
  \*Characteristic impedance: 75 ohm, and insulation thickness: 3 mm.

#### **Standard Accessories**

- Quick guide.....1 pc
- Important safety instruction.....1 pc


#### Appearance



#### Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.

|   | Parameter               | CV-CFW103L  | CV-CFW103LN      |
|---|-------------------------|---|------------------|
|   | Camera                  |   |                  |
|   | Image Sensor            | 1/2.9" 1.0 Mega Pixels CMOS   |                  |
|   | Effective Pixels        | 1280 (H) × 720 (V)  |                  |
|   | Min Illumination        | 0.05Lux/ F1.6, 0Lux IR on   |                  |
| d | Electronic Shutter      | 1/50s~1/100,000s  | 1/60s~1/100,000s |
|   | Video Frame Rate        | 25fps   | 30fps            |
|   | Synchronization         | Internal  |                  |
|   | Day & Night             | Auto (ICR)/ Color/ B/W  |                  |
|   | Max IR Distance         | 30m   |                  |
|   | Digital Noise Reduction | 2D  |                  |
|   | White Balance           | Auto  |                  |
|   | AGC                     | Auto  |                  |
|   | BLC                     | Auto  |                  |
|   | Lens                    |   |                  |
|   | Focal Length            | 3.6 mm  |                  |
|   | Angular Field of View   | H: 88° V: 46°<br>M12  |                  |
|   | Lens Type               |   |                  |
|   | Input / Output          |   |                  |
|   | Video Output            | 1 CH BNC HD-CVI video output  |                  |
|   | General                 |   |                  |
|   | Power                   | DC 12V±25%        2.5W MAX        -30°C~+60°C.        Less than 95% RH (no condensation)        Ф93.4 mm x 79.7 mm        350g        Wall mount/ In-ceiling mount        Metal |                  |
|   | Power Consumption       |   |                  |
|   | Working Temperature     |   |                  |
|   | Dimensions              |   |                  |
|   | Weight (approx.)        |   |                  |
|   | Installation Mode       |   |                  |
|   | External Case           |   |                  |



Ø68.1 Ø93.4

- Weights and dimensions are approximate.
- Specifications are subject to change without notice.

These products may be subject to export control regulations.

#### **DISTRIBUTED BY:**