HD Analog Day/ Night Fixed IR Dome Camera

Panasonic

CV-CFN103L CV-CFN103LN

Smart look Indoor Day/ Night Fixed Dome Camera with IR illuminator






Key Features


- High-performance CMOS image sensor.
- Support 720p@25fps (PAL)/ 30fps (NTSC)
- Support 75-3 coaxial cable transmission over 800m.
- High speed & long distance real-time transmission.
- Support ICR for day time and night time operation.
- Support auto exposure, auto white balance, auto electronic shutter and auto gain function.
- Support DC12V power supply.

Standard Accessories

Quick guide......1 pc Important safety instruction......1 pc

Appearance





Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.
- All pictures are simulated.Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

| Specifications | | |
|-------------------------|--|------------------|
| Parameter | CV-CFN103L | CV-CFN103LN |
| Camera | | |
| Image Sensor | 1/2.9" 1.0 Mega Pixels CMOS | |
| Effective Pixels | 1280 (H) x 720 (V) | |
| Min Illumination | 0.05Lux/ F1.6, 0Lux IR on | |
| Electronic Shutter | 1/50s~1/100,000s | 1/60s~1/100,000s |
| Video Frame Rate | 25fps | 30fps |
| Synchronization | Internal | |
| Day & Night | Auto (ICR)/ Color/ B/W | |
| Max IR Distance | 20m | |
| Digital Noise Reduction | 2D | |
| White Balance | Auto | |
| AGC | Auto | |
| BLC | Auto | |
| Lens | | |
| Focal Length | 3.6 mm | |
| Angular Field of View | H: 88° V: 46° | |
| Lens Type | M12 | |
| Input / Output | | |
| Video Output | 1 CH BNC HD-CVI video output | |
| General | | |
| Power | DC 12V±25% | |
| Power Consumption | 2.2W MAX | |
| Working Temperature | -30°C∼+60°C. Less than 95% RH (no condensation) | |
| Dimensions | Ф85 mm × 69 mm | |
| Weight (approx.) | 100g | |
| Installation Mode | Wall mount/ In-ceiling mount | |
| External Case | Plastic | |

DISTRIBUTED BY: