

CP- ENR-4532**32 Ch. Network Video Recorder****Main Features**

- Up to 5MP resolution preview and playback
- H.265/ H.264 Video Compression
- Support 4 SATA HDDs up to 24TB, 2 USB (1 USB 3.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Supports
- Mobile Software: RMOB
- CMS Software: RVMS



CP- ENR-4532

32 Ch. Network Video Recorder



Feature

Processor
Operating System
IP Camera Input
System Resources
User Interface
Video Input
Video Output
Compression
Video Resolution
Video Display Split
Audio Input
Audio Output
Motion Detection
Alarm Input
Alarm Output
Smart Phone
Hard Disk
Recording Mode
Search Mode
Playback
Backup Mode
Interface Ports
Ethernet
Protocols
Power Supply
Power Consumption
Working Temp
Dimensions
Weight

Specification

Dual-core embedded processor
Embedded LINUX
32 channel
Simultaneous multi-channel real-time recording, playback, network operation, USB backup
GUI
32Ch. @4MP / 24Ch. @5MP / 16Ch. @1080P
1 HDMI, 1 VGA, Support VGA HDMI 4K output
H.265/ H.264/ G.711A
2560 × 1920, 2048 × 1536, 1920 × 1080, 1280 × 1024, 1280 × 720, 1024 × 768
1/4/8/16/24/32
1 Channel
1 Channel
Supports
16 Channel
4 Channel
iPhone, iPad, Android Phone
4 SATA ports, up to 24TB
Manual, Alarm, Video Detection, Continuous
Search by Time/calendar/event/channel
9Ch. @4MP / 4Ch. @5MP/ 16Ch. @1080P
Network backup, USB hard disk, USB burner, SATA burner
1 HDMI, 1 VGA, 2 USB(1 USB 3.0), 1 RJ45, 1 RS485
1 RJ-45 port (10/100/1000M)
HTTP, TCP/IP, UDP, IPV4/IPV6, UPNP, RTSP, SMTP, NTP, DHCP, DNS, FTP, P2P, ONVIF, CGI
12V/ 6A
<10W(Without HDD)
0°C- +55°C / 10%—90%RH / 86kpa—106kp
440mm x 400.5mm x 60mm
Around 1.6 Kg