



HIGH VOLTAGE OBTUSE ANGLE ELECTRICAL TERMINALS SHORT BARREL ONE HOLE

หางปลาแรงสูงชนิดรูเดียว 135°

(HOS TYPE)

Suitable for use with cable size from
10-500 SQ.MM.in 135° angle position

Material: Copper tube Cu 99% up


Surface: Tin plated



WIRE CONNECTOR

3LDJ

FILE No: E304648



Item No.	TIS Wire Size mm ²	DIMENSIONS (MM.)												Q'TY in box
		d2ø	d1ø	Dø	A	B	E	F	H	L	M	N	T	
HOS 10-6	10	6.4	4.5	6.2	9.5	12.0	21.5	7.4	16.5	26.0	50.8	21.5	1.1	100
HOS 10-8		8.4												
HOS 16-6	16	6.4	5.4	7.1	9.5	12.0	25.0	7.4	16.5	26.0	53.9	24.1	1.2	100
HOS 16-8		8.4												
HOS 25-6	25	6.4	6.8	8.8	11.5	15.0	28.5	7.4	18.5	30.0	61.6	27.0	1.6	100
HOS 25-8		8.4												
HOS 25-10		10.5												
HOS 35-6	35	6.4	8.2	10.6	11.5	17.0	32.0	8.0	21.5	33.0	68.8	30.3	2.0	50
HOS 35-8		8.4												
HOS 35-10		10.5												
HOS 50-8	50	8.4	9.5	12.4	13.5	19.0	35.0	10.9	23.5	37.0	78.2	35.0	2.5	40
HOS 50-10		10.5												
HOS 50-12		13.0												
HOS 70-8	70	8.4	11.2	14.7	13.5	21.0	35.0	10.9	27.5	41.0	83.8	36.0	3.5	40
HOS 70-10		10.5												
HOS 70-12		13.0												
HOS 95-8	95	8.4	13.5	17.4	13.5	25.5	38.0	15.8	27.5	41.0	91.3	41.6	3.6	20
HOS 95-10		10.5												
HOS 95-12		13.0												
HOS 120-10	120	10.5	15.0	19.4	14.5	28.0	40.0	18.8	28.5	43.0	98.3	45.9	4.3	20
HOS 120-12		13.0												
HOS 120-14		15.0												
HOS 150-12	150	13.0	16.5	21.2	16.5	30.5	50.0	19.8	30.5	47.0	111.3	53.8	4.5	10
HOS 150-14		15.0												
HOS 150-16		17.0												
HOS 185-12	185	13.0	18.5	23.5	16.5	34.0	50.0	19.8	30.5	47.0	113.0	54.1	4.8	5
HOS 185-14		15.0												
HOS 185-16		17.0												
HOS 240-12	240	13.0	21.5	27.0	16.5	39.5	56.0	24.8	35.5	52.0	127.9	62.6	5.5	5
HOS 240-14		15.0												
HOS 240-16		17.0												
HOS 300-12	300	13.0	23.5	30.0	20.0	43.5	67.0	26.8	44.0	64.0	151.5	72.6	6.3	5
HOS 300-14		15.0												
HOS 300-16		17.0												
HOS 400-12	400	13.0	27.0	35.0	23.0	50.8	67.0	26.8	47.0	70.0	155.9	74.2	7.9	1
HOS 400-14		15.0												
HOS 400-16		17.0												
HOS 500-12	500	13.0	30.0	39.0	23.0	56.0	75.0	33.8	47.0	70.0	169.9	85.8	8.9	1
HOS 500-14		15.0												
HOS 500-16		17.0												