



ห้างหุ้นส่วนจำกัด แจ็คคอนเน็คท์ไฟฟ้า (สำนักงานใหญ่)

เลขที่ 39/305 โครงการศุภลักษณ์ หมู่ที่ 4 ถนนพื้งสุขอุทิศ ตำบลบึงคำพร้อย อำเภอลำลูกกา

จังหวัดปทุมธานี 12150 โทร.065-5539655 , 02-0038362 e-mail : chokeng16@hotmail.com

www.chokeng.com , Line : @jackconnect

Product Specification

White Non-Braided Gasket Rope

Product Description

White Non-Braided Gasket Rope is a rope-type sealing material manufactured from multiple heat-resistant fibers twisted together without a braiding process. It is designed for caulking and sealing applications in high-temperature systems, as well as for thermal insulation in industrial heat-transfer equipment.



Key Features

- High temperature resistance suitable for industrial thermal systems
- Flexible structure providing excellent sealing and gap-filling performance
- Good resistance to common industrial chemicals
- Easy installation, ideal for maintenance and repair applications

Technical Specification

Item	Description
Product Type	Non-Braided Gasket Rope
Construction	Twisted fiber structure (Non-Braided)
Service Temperature	Approx. 250 – 550 °C
Diameter Range	6 – 50 mm
Color	White
Flexibility	Suitable for sealing and caulking applications
Typical Applications	Sealing / Caulking / Thermal insulation

Recommended Applications

- Industrial piping and thermal systems
- Industrial furnaces and ovens
- Thermal insulation in heat-transfer systems
- Industrial maintenance and repair work

Note: Product performance may vary depending on actual operating conditions. Selection and use should comply with applicable safety regulations and standards.