Panasonic

CJ-HDR416

16 CH HDCVI 4 SATA HDD Analog Digital Video Recorder




Key Features

- 16 CH with 1080p real time live view
- H.264 video encode
- 1/4/9/16 CH synchronous real time playback
- HDMI/ VGA/ TV simultaneous video output
- Support 4 SATA HDDs up to 24TB, 3 USB
- Digital Zoom in Live & Playback
- iPhone, iPad & Android

Standard Accessories

•	Quick guide1pc
•	Important safety instruction1 pe
•	CD1p

Appearance



Specifications

Model		CJ-HDR416
Video/ Audio I	F	
Video Input		16 CH, BNC
-	HDCVI	720p/ 1080p HDCVI
Туре	Analog	NTSC/ PAL
Video Output		1 HDMI, 1 VGA, 1 TV
Audio Input		4 CH, BNC
Audio Output		1 CH, BNC
Two-way Talk		1 CH input, 1 CH output, BNC
Display		
Output Resolut	tion	1920×1080, 1280×1024, 1280×720, 1024×768
Multiscreen Mode		1/4/8/9/16
Privacy Masking		4 rectangular zones (each camera)
OSD		Camera title, Time, Video loss, Camera lock, Motion detection,
		Recording
Video/ Audio I	Format	
Video/Audio Co	ompression	H.264/ G.711
December 19:4:	Main Stream	1080P (1~12/15fps)/ 720P/ 960H/ D1/ HD1/ 2CIF/ CIF (1~25/30fps
Record Rate	Extra Stream	CIF/ QCIF (1~25/30fps), D1 (1~12/15fps)
Bit Rate		48~4096Kb/s
Record Mode		Manual, Schedule (Regular (Continuous), MD), Stop
Record Interval		1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Alarm/ Event		
Trigger Events		Recording, PTZ, Tour, Alarm out, Video Push, Email, FTP, Spot, Snapshot, Buzzer & Screen tips
Video Detection		Motion Detection, MD Zones: 396 (22×18), Video Loss & Camera Blank
Playback & Ba	ackup	
Sync Playback	·	1/4/9/16
Search Mode		Time/Date, MD & Exact search (accurate to second)
Playback Functions		Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previou file, Next camera, Previous camera, Full screen, Repeat, Shuffle,
Playback Func	tions	
•	tions	Backup selection, Digital zoom
Backup Mode	tions	
Backup Mode Network		Backup selection, Digital zoom USB Device/ eSATA Device/ Network
Backup Mode	ace	Backup selection, Digital zoom
Backup Mode Network Network Interfa	ace	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP,
Backup Mode Network Network Interfa Network Funct Max. User Acc	ace	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P 128 users
Backup Mode Network Network Interfa Network Funct Max. User Acc Mobile Device	ace	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P
Backup Mode Network Network Interfa Network Funct Max. User Acc Mobile Device HDD	ace	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P 128 users iPhone, iPad, Android
Backup Mode Network Network Interfa Network Funct Max. User Acc Mobile Device HDD Type	ace ions ess	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P 128 users
Backup Mode Network Network Interfa Network Funct Max. User Acc Mobile Device HDD Type External Interfa	ace ions ess	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P 128 users iPhone, iPad, Android 4 SATA ports, up to 24TB
Backup Mode Network Network Interfa Network Funct Max. User Acc Mobile Device HDD Type External Interfa USB Interface	ace ions ess	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P 128 users iPhone, iPad, Android 4 SATA ports, up to 24TB 3 ports (2 Rear), USB2.0
Backup Mode Network Network Interfa Network Funct Max. User Acc Mobile Device HDD Type External Interf USB Interface RS485 Camera	ace ions ess face a Interface	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P 128 users iPhone, iPad, Android 4 SATA ports, up to 24TB
Backup Mode Network Network Interfa Network Funct Max. User Acc Mobile Device HDD Type External Interf USB Interface RS485 Camera General Speci	ace ions ess face a Interface	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P 128 users iPhone, iPad, Android 4 SATA ports, up to 24TB 3 ports (2 Rear), USB2.0 1 port RS485 for PTZ control,1 port RS422 for Keyboard
Backup Mode Network Network Interfa Network Funct Max. User Acc Mobile Device HDD Type External Interfa USB Interface RS485 Camera General Speci	face a Interface ifications	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P 128 users iPhone, iPad, Android 4 SATA ports, up to 24TB 3 ports (2 Rear), USB2.0 1 port RS485 for PTZ control,1 port RS422 for Keyboard AC 100~240 V, 50/60 Hz
Backup Mode Network Network Interfa Network Funct Max. User Acc Mobile Device HDD Type External Interface RS485 Camera General Speci Power Supply Power Consum	face a Interface ifications	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P 128 users iPhone, iPad, Android 4 SATA ports, up to 24TB 3 ports (2 Rear), USB2.0 1 port RS485 for PTZ control,1 port RS422 for Keyboard AC 100~240 V, 50/60 Hz 40W (without HDD)
Backup Mode Network Network Interfa Network Funct Max. User Acc Mobile Device HDD Type External Interfa USB Interface RS485 Camera General Speci	face a Interface a Interface ifications apption anoment	Backup selection, Digital zoom USB Device/ eSATA Device/ Network RJ-45 port (10/100M/ 1000M) HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, SNMP, P2P 128 users iPhone, iPad, Android 4 SATA ports, up to 24TB 3 ports (2 Rear), USB2.0 1 port RS485 for PTZ control,1 port RS422 for Keyboard AC 100~240 V, 50/60 Hz

Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.

- All pictures are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.
- These products may be subject to export control regulations.

DISTRIBUTED BY: